

## EagleEye International Ltd.

Wentshaw Lodge, Fairseat, Sevenoaks, Kent, TN15 7LR, UK

<http://www.eagleeyeuk.com>

### Wing Bracket Locating Strut

For Use with Xtend-a-View™ Pro LCD Viewer & Sunshade

XVP Standard for CP950/CP990/CP995 and XVP Mini for CP4500

Thank you for choosing EagleEye products. Please take great care when fitting this Support Strut to your Xtend-a-View Pro™ Viewer. Do not force or bend the strut.

This item is designed for use in conjunction with the Xtend-a-View™ Pro LCD Viewer and Sunshade for use with the EagleEye Wing / Wing II / Wing 4500 Brackets.

The smaller end of the Support Stud is eccentric for both the 950 and 990/995 studs. The stud for the 4500 is straight.

To fit the strut permanently it is necessary to apply a **very small** amount of adhesive to the small stud portion before inserting it into the locating hole of the LCD Viewer & Sunshade. Extreme Care should be taken when using adhesives.

There are 2 small locating holes which can be found at the base of Xtend-a-View Pro, one on each side. With the Wing Bracket fixed to the camera and the Xtend-a-View Pro positioned correctly against the camera LCD panel and looking from the back of the camera (the normal holding position), the small locating hole in the Wing Bracket is found on the left hand side.

The hole on the LCD Viewer & Sunshade into which the Support Stud fixes is the one also located on the left hand side.

Attach the rubber, supplied with the Xtend-a-View Pro (cut into strips) to the front 3 edge faces of the Viewer & Sunshade (left / top / right) as shown in the instructions for the viewer. Alternatively, you may use the Velcro strip.

Then place a very small amount of adhesive such as Loctite adhesive onto the smaller end of the mounting strut (do not use instant setting adhesive). Then carefully push the Support Stud into the hole on the Viewer & Sunshade. It should be pushed in until the strut "bottoms out" against the Xtend-a-View Pro body. For the 950 stud and 990/995 studs, align the small dimple on the stud as shown in the picture.

At this point ensure that there is no surplus adhesive. Then fit the Support Stud with the Xtend-a-View Pro attached into the Wing Bracket locating hole. Secure in place using the small supplied Support Stud thumbscrew.

The Xtend-a-View Pro and the Support Stud should then be gently adjusted until the Viewer & Sunshade are correctly aligned with the camera LCD panel and lay flat against it. Gently place the entire assembly down without disturbing the alignment and leave it alone until it has hardened before use.

Copyright © 2003 EagleEye International Ltd.

